

MICHELIN® CROSS TERRAIN™ SUV

UTQG RATING

TREADWEAR	700+ (S-Rated)	520 (H-Rated)	420**
TRACTION	A	A	A
TEMPERATURE	B	A	B

(*effective mid-2002)

Tire Size	Service Description	Sidewall	MSPN	Rim Width Range	Section Width on Measuring Rim Width (inches)	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max Load* (lbs=psi)
P215/75R15	100S	ORWL	81537	5.5 - 7.0	8.5 on 6.0	27.7	11.5	751	1584 @ 35
P225/70R15	100S	ORWL	49565	6.0 - 7.5	9.0 on 6.5	27.5	11.5	756	1594 @ 35
P225/75R15	102S	ORWL	77587	6.0 - 7.5	8.9 on 6.0	28.2	11.5	742	1704 @ 35
P235/70R15	102S	ORWL	60547	6.0 - 8.0	9.5 on 7.0	28.0	11.5	743	1724 @ 35
P235/75R15	105S	ORWL	73546	6.0 - 8.0	9.4 on 6.5	28.8	11.5	726	1844 @ 35
P265/70R15	110S	ORBL	96459	7.0 - 9.0	10.7 on 8.0	29.7	11.5	700	2125 @ 35
P225/70R16	101S	ORWL	75883	6.0 - 7.5	9.0 on 6.5	28.3	11.5	741	1654 @ 35
P225/75R16	104S	ORWL	48514	6.0 - 7.5	8.8 on 6.0	29.3	11.5	710	1804 @ 35
P235/70R16	104S	ORWL	79176	6.0 - 8.0	9.5 on 7.0	29.1	11.0	712	1804 @ 44
P245/70R16	106S	ORWL	97768	6.5 - 8.0	9.7 on 7.0	29.5	11.5	709	1904 @ 35
P245/75R16	109S	ORWL	89325	6.5 - 8.0	9.7 on 7.0	30.2	11.5	691	2065 @ 35
P255/65R16	109H	ORBL	87981	7.0 - 9.0	10.2 on 7.5	29.0	11.0	717	2065 @ 36
P255/70R16	109S	ORWL	67119	6.5 - 8.5	10.2 on 7.5	30.2	11.5	693	2065 @ 35
P265/70R16	111S	ORBL	56411	7.0 - 9.0	10.8 on 8.0	30.6	11.5	680	2185 @ 35
P265/70R16	111S	ORWL	64353	7.0 - 9.0	10.8 on 8.0	30.6	11.5	680	2185 @ 35
P265/75R16	114S	ORWL	89355	7.0 - 9.0	10.5 on 7.5	31.7	11.5	656	2365 @ 35
P275/70R16	114S	ORBL	57546	7.0 - 9.0	11.0 on 8.0	31.2	11.5	667	2365 @ 35
P235/65R17	103T	ORBL	95648	6.5 - 8.5	9.0 on 6.5	28.9	11.0	726	1754 @ 35
P245/65R17	105S	ORBL	87242	7.0 - 8.5	9.6 on 7.0	29.6	11.0	702	1854 @ 35
P255/60R17	105S	ORBL	65887	7.0 - 9.0	10.2 on 7.5	29.1	10.5	711	1854 @ 35
P255/75R17	113S	ORBL	42718	6.5 - 8.5	10.1 on 7.0	32.1	11.5	648	2305 @ 44
P265/70R17	113S	ORBL	61797	7.0 - 9.0	10.7 on 8.0	31.9	12.0	652	2305 @ 35
P265/70R17	113H	ORBL	60704	7.0 - 9.0	10.7 on 8.0	31.7	11.0	656	2305 @ 35
P265/70R17*	113S	ORWL	61677	7.0 - 9.0	10.7 on 8.0	31.9	12.0	652	2305 @ 35
P275/55R17	109H	ORBL	48296	7.5 - 9.5	11.2 on 8.5	28.9	11.0	720	2065 @ 36
P275/60R17	110S	ORWL	88696	7.5 - 9.5	11.0 on 8.0	30.0	11.5	693	2125 @ 35
P275/60R17	110H	ORBL	47206	7.5 - 9.5	11.0 on 8.0	30.0	11.0	693	2125 @ 35
P255/70R18	112S	ORBL	84179	6.5 - 8.5	10.2 on 7.5	32.2	12	643	2245 @ 44
P275/55R18	109S	ORBL	61247	7.5 - 9.5	10.5 on 7.5	30.1	11.5	691	2064 @ 35

*Load reduced 9.1% for Light Truck/SUV application. This will differ from maximum load branded on tire sidewall.

Michelin® tires and tubes are subject to a continuous development program. Michelin North America, Inc. reserves the right to change product specifications at any time without notice or obligation.

1. The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.

2. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width. WARNING: Serious or fatal injury may result from improper mounting, from under-inflation/over-inflation/over-loading or from tire damage due to abusive use. For proper mounting, see tire dealer. For proper tire size and inflation pressure, consult Tire Information Placard in vehicle.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual. For speeds over 100 mph, load and inflation must be adjusted according to the table below.

H-Speed Rated Sizes:

Maximum Speed (mph)	100	106	112	118	124	130
Inflation Increase (psi)	0.0	1.0	2.0	3.0	4.0	5.0
Load Capacity (% of max.)	100	100	100	100	100	100

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a consumer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

** All OE sizes: P235/70R16, P235/65R17, P245/65R17, P255/60R17, P265/70R17, P275/55R18, P255/70R18

* Available Q4 2002

EXCEPTIONAL WET BRAKING and low noise levels due to revolutionary silica tread compound and tread design.

EXCEPTIONAL WET AND SNOW TRACTION with excellent tread block stability enabled by full-depth, interlocking sipes.

RESPONSIVE HANDLING and even wear provided by a square, stable contact patch and enhanced casing system.

BOLD, RUGGED LOOKING APPEARANCE enhanced by a unique sidewall design, optional black-wall or raised white lettering and the rich look of new DURABLACK™ technology.

IMPROVED RIDE COMFORT and handling due to new bead design and Bead Tension Structure.™

ADDED STRENGTH AND DURABILITY provided by larger cables in the steel belts.

