

UTQG RATING:

Description	Treadwear	Traction	Temperature
Tiger Paw® AWP			
P145/80R13, P155/80R13	460	A	B
All Other 13"	480	A	B
All 14"	580	A	B
P205/75R15 OE Version	480	B	B
P215/75R15 OE Version	500	B	B

Description	Treadwear	Traction	Temperature
Cont.			
P235/75R15 OE Version	500	B	B
All Other 15"	580	A	B
P225/60R16 OE Version	500	B	B
All Other 60/65 Series Sizes	540	A	B

Tire Size	Service Desc.	Sidewall	MSPN	Stock Number	Rim Width Range (in.)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Rev/Mile at 45 mph	Single (lbs@psi)
P155/80R13	79S	BSW	65657	146-782	4.0 - 5.5	6.3 on 4.5	22.8	9.0	912	959@35
P175/70R13	82S	BSW	96224	146-308	4.5 - 6.0	6.9 on 5.0	22.6	9.5	920	1036@35
P185/70R13	85S	BSW	73566	146-311	4.5 - 6.5	7.4 on 5.5	23.2	11.0	897	1135@35
P185/75R14	89S	0.65	65842	147-627	4.5 - 6.5	7.2 on 5.0	25.0	11.0	832	1290@35
P195/75R14	92S	0.65	71996	147-628	5.0 - 7.0	7.7 on 5.5	25.5	11.0	816	1400@35
P195/75R14	92S	BSW	63864	146-628	5.0 - 7.0	7.7 on 5.5	25.5	11.0	816	1400@35
P205/75R14	95S	0.65	88243	147-629	5.0 - 7.5	8.0 on 5.5	26.1	11.0	797	1532@35
P205/75R14	95S	ROWL	75819	145-629	5.0 - 7.5	8.0 on 5.5	26.1	11.0	797	1532@35
P215/75R14	98S	0.65	75666	147-647	5.5 - 7.0	8.5 on 6.0	26.7	11.0	779	1664@35
P175/70R14	84S	BSW	68672	146-391	4.5 - 6.0	7.0 on 5.0	23.7	11.0	874	1102@35
P185/70R14	87S	0.65	99458	147-410	4.5 - 6.5	7.4 on 5.5	24.3	11.0	856	1201@35
P185/70R14	87S	BSW	53875	146-410	4.5 - 6.5	7.4 on 5.5	24.3	11.0	856	1201@35
P195/70R14	90S	BSW	67631	146-413	5.0 - 7.0	7.9 on 6.0	24.8	11.0	839	1312@35
P205/70R14	93S	0.65	74126	147-416	5.0 - 7.5	8.2 on 6.0	25.4	11.0	819	1433@35
P215/70R14	96S	0.65	88837	147-420	5.5 - 7.5	8.7 on 6.5	25.9	11.0	803	1554@35
P215/70R14	96S	ROWL	50556	145-420	5.5 - 7.5	8.7 on 6.5	25.9	11.0	803	1554@35
P175/65R14	81S	BSW	77816	146-378	5.0 - 6.0	7.0 on 5.0	23.0	10.5	904	1019@35
P185/65R14	85S	BSW	91956	146-178	5.0 - 6.5	7.2 on 5.5	23.3	9.5	892	1124@35
P205/75R15	97S	0.75	40929	147-614	5.0 - 7.5	8.0 on 5.5	27.1	11.0	768	1598@35
P205/75R15	97S	BSW	75687	146-614	5.0 - 7.5	8.0 on 5.5	27.1	11.0	768	1598@35
P205/75R15	97S	BSW	61714†	192-614†	5.0 - 7.5	8.0 on 5.5	27.1	11.0	768	1598@35
P205/75R15	97S	ROWL	83014	145-614	5.0 - 7.5	8.0 on 5.5	27.1	11.0	768	1598@35
P215/75R15	100S	0.75	71632	147-615	5.5 - 7.5	8.5 on 6.0	27.7	11.0	751	1742@35
P215/75R15	100S	BSW	53938	146-615	5.5 - 7.5	8.5 on 6.0	27.7	11.0	751	1742@35
P215/75R15	100S	ROWL	60628	145-615	5.5 - 7.5	8.5 on 6.0	27.7	11.0	751	1742@35
P225/75R15	102S	0.75	67235	147-616	6.0 - 8.0	8.8 on 6.0	28.3	11.0	735	1874@35
P225/75R15	102S	ROWL	75500	145-616	6.0 - 8.0	8.8 on 6.0	28.3	11.0	735	1874@35
P235/75R15	105S	0.75	72817	147-649	6.0 - 8.0	9.3 on 6.5	28.9	11.0	720	2028@35
P235/75R15	105S	BSW	79551*	146-649	6.0 - 8.0	9.0 on 6.5	28.7	10.0	725	2028@35
P235/75R15	105S	ROWL	43266*	146-649	6.0 - 8.0	9.3 on 6.5	28.9	11.0	720	2028@35
P235/75R15/XL	108S	0.75	50797	147-703	6.0 - 8.0	9.0 on 6.5	28.8	10.0	722	2183@41
P235/75R15/XL	108S	BSW	43490	146-703	6.0 - 8.0	9.0 on 6.5	28.8	10.0	722	2183@41
P235/75R15/XL	108S	ROWL	72600	145-703	6.0 - 8.0	9.0 on 6.5	28.8	10.0	722	2183@41
P205/70R15	95S	0.75	68591	147-658	5.0 - 7.5	8.2 on 6.0	26.3	11.0	791	1499@35
P205/70R15	95S	BSW	73690	146-658	5.0 - 7.5	8.2 on 6.0	26.3	11.0	791	1499@35
P215/70R15	97S	0.75	78230	147-639	5.5 - 7.5	8.7 on 6.5	26.9	11.0	773	1620@35
P215/70R15	97S	BSW	87816	146-639	5.5 - 7.5	8.7 on 6.5	26.9	11.0	773	1620@35
P225/70R15	100S	0.75	83299	147-523	6.0 - 8.0	9.0 on 6.5	27.4	11.0	759	1753@35
P225/70R15	100S	BSW	78521	146-523	6.0 - 8.0	9.0 on 6.5	27.4	11.0	759	1753@35
P225/70R15	100S	BSW	63103†	340-523†	6.0 - 8.0	9.0 on 6.5	27.4	10.0	759	1753@35
P235/70R15	102S	0.75	40215	147-543	6.5 - 8.0	9.5 on 7.0	28.0	11.0	743	1896@35
P185/65R15	86S	BWS	81918	106-283	5.0 - 6.5	7.5 on 5.5	24.4	9.5	856	1168@35
P195/65R15	89S	BSW	69497	146-362	5.5 - 7.0	7.9 on 6.0	25.0	11.0	832	1279@35
P205/65R15	92S	BSW	71629	146-580	5.5 - 7.5	8.2 on 6.0	25.5	11.0	816	1400@35
P215/65R15	95S	BSW	72879	146-587	6.0 - 7.5	8.7 on 6.5	26.0	11.0	800	1510@35
P215/65R16	96S	BSW	47145	102-600	6.0 - 7.0	9.8 on 6.5	26.9	11.0	773	1565@35
215/65R16	98S	BSW	59373	272-862	6.0 - 7.5	8.2 on 6.5	27.0	13.0	770	1653@44
P225/60R16	97S	BSW	67415	146-274	6.0 - 8.0	9.8 on 6.5	27.0	9.5	770	1609@35
225/60R16	98S	ROWL	45985	295-555	6.0 - 8.0	8.7 on 6.5	26.9	10.0	773	1653@44
**Tiger Paw AWP With NailGard										
215/65R16	98S	BSW	80135	278-862	6.0 - 7.5	8.2 on 6.5	27.0	13.0	770	1653@44

*These MSPN's are not Ford authorized replacement tires (i.e., Ford Explorer). Contact Consumer Relations for tires that are authorized.

**UTQG Rating: 500 A B

NOTE: Original Equipment sizes may be branded B traction grade.

†Designed for use on electric vehicles.

The dimensions shown are average values for tires measured on the specified measuring rim width. Individual tires may vary from data shown. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

WARNING: Serious or fatal injury may result from improper mounting, from underinflation or overloading, or from tire damage due to abusive use. For proper mounting, see tire dealer. For proper operation, consult Tire Information Placard in vehicle. For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual:

For speeds over 100 mph, load and inflation MUST be adjusted according to the table below.

MAXIMUM SPEED mph	100	106	112
INFLATION INCREASE psi	0	1	2
LOAD CAPACITY (% of max)	100	100	100

S-rated tires limited to 112 mph.

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a consumer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different and that its maximum speed capability is limited to that of the lowest speed rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.