

**UTQG RATING:**

Description	Treadwear	Traction	Temperature
Tiger Paw® with NailGard®			
70/75 Series			
All 13"	560	A	B
All 14" & 15"	640	A	B
60/65 Series	600	A	B

Tire Size	Service Desc.	Sidewall	MSPN	Stock Number	Rim Width Range (in.)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Rev/Mile at 45 mph	Single (lbs@psi)
P175/70R13	82S	BSW	66945	342-308	4.5 - 6.0	7.0 on 5.0	22.7	11.0	916	1036@35
P205/75R14	95S	0.65	43095	343-629	5.0 - 7.0	8.0 on 5.5	26.1	11.5	797	1532@35
P185/70R14	87S	BSW	47911	342-410	4.5 - 6.0	7.4 on 5.5	24.3	11.0	856	1201@35
P195/70R14	90S	BSW	66922	342-413	5.0 - 6.5	7.9 on 6.0	24.8	11.0	839	1312@35
P205/70R14	93S	BSW	68297	342-416	5.0 - 7.0	8.2 on 6.0	25.4	11.5	819	1433@35
P185/65R14	85S	BSW	78911	342-178	5.0 - 6.5	7.4 on 5.5	23.5	10.5	885	1124@44
P215/75R15	100S	0.75	66124	343-615	5.5 - 7.0	8.5 on 6.0	27.7	11.5	751	1742@35
P225/75R15	102S	0.75	41046	343-616	6.0 - 7.5	8.8 on 6.0	28.3	11.5	735	1874@35
P235/75R15	105S	0.75	62433	343-649	6.0 - 8.0	9.3 on 6.5	28.9	11.5	720	2028@35
P205/70R15	95S	0.75	75711	343-658	5.0 - 7.0	8.2 on 6.0	26.3	11.5	791	1499@35
P215/70R15	97S	0.75	91390	343-639	5.5 - 7.0	8.7 on 6.5	26.9	11.5	773	1620@35
P235/70R15	102S	0.75	84809	343-543	6.0 - 8.0	9.5 on 7.0	28.0	11.5	743	1896@35
P195/65R15	89S	BSW	50293	342-362	5.5 - 7.0	7.9 on 6.0	25.0	10.5	832	1279@44
P205/65R15	92S	BSW	94514	342-580	5.5 - 7.5	8.2 on 6.0	25.5	10.5	816	1400@44
P215/65R15	95S	BSW	67495	342-587	6.0 - 7.5	8.7 on 6.5	26.0	10.5	800	1510@44
P195/60R15	87S	BSW	57169	342-487	5.5 - 7.0	7.9 on 6.0	24.3	10.5	856	1190@44
P215/60R16	94S	BSW	79573	342-278	6.0 - 7.5	8.7 on 6.5	26.1	10.5	797	1477@44
P225/60R16	97S	BSW	56046	342-274	6.0 - 8.0	9.0 on 6.5	26.6	10.5	782	1609@44

The dimensions shown are average values for tires measured on the specified measuring rim width. Individual tires may vary from data shown. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width.

**WARNING:** Serious or fatal injury may result from improper mounting, from underinflation or overloading, or from tire damage due to abusive use. For proper mounting, see tire dealer. For proper operation, consult Tire Information Placard in vehicle. For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual:

For speeds over 100 mph, load and inflation **MUST** be adjusted according to the table below.

MAXIMUM SPEED mph	100	106	112
INFLATION INCREASE psi	0	1	2
LOAD CAPACITY (% of max)	100	100	100

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a consumer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different and that its maximum speed capability is limited to that of the lowest speed rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

