

Tire Size	Service Description	Sidewall	MSPN	Rim Width Range (inches)	Section Width on Measuring Rim Width	Overall Diameter	Tread Depth (in/32nds)	Revs/Mile at 45 mph	Max Load (lbs=psi)
P175/65R14	81T	BW	56190	4.5 - 6.0	6.8 on 5.0	23.0	11	914	1019@35
P175/70R14	84T	BW	42395	4.5 - 6.0	6.9 on 5.0	23.5	11	893	1102@35
P185/60R14	82T	BW	73854	5.0 - 7.0	7.4 on 5.5	22.8	11	918	1047@35
P185/65R14	85T	BW	64484	5.0 - 6.5	7.4 on 5.5	23.4	11	901	1124@35
P185/70R14	87T	BW	55309	4.5 - 6.5	7.4 on 5.5	24.1	11	870	1201@35
P195/60R14	85T	BW	63736	4.5 - 7.5	7.9 on 6.0	23.1	11	880	1135@35
P195/65R14	88T	BW	83114	5.0 - 7.0	8.0 on 6.0	23.9	11	880	1235@35
P195/70R14	90T	BW	72034	5.0 - 7.0	8.0 on 6.0	24.6	11	851	1312@35
P205/70R14	93T	BW	76911	5.0 - 7.5	8.4 on 6.0	25.1	12	837	1433@35
P215/70R14	96T	BW	67801	5.5 - 7.5	8.9 on 6.5	25.6	12	820	1554@35
P185/65R15	86T	BW	76901	4.5 - 6.5	7.4 on 5.5	24.4	11	859	1168@35
P195/60R15	87T	BW	88090	4.5 - 7.5	7.9 on 6.0	24.1	11	867	1190@35
P195/65R15	89T	BW	44733	5.0 - 7.0	7.8 on 6.0	24.8	11	841	1279@35
P205/60R15	90T	BW	84745	5.0 - 8.0	8.3 on 6.0	24.6	11	854	1301@35
P205/65R15	92T	BW	87297	5.0 - 7.5	8.2 on 6.0	25.3	11	826	1400@35
P205/70R15	95T	VVV	47042	5.5 - 7.5	8.4 on 6.0	26.1	12	802	1499@35
P205/70R15	95T	BW	48873	5.5 - 7.5	8.4 on 6.0	26.1	12	802	1499@35
P215/65R15	95T	BW	82216	5.5 - 7.5	8.8 on 6.5	25.8	11	812	1510@35
P215/70R15	97T	VVV	76697	5.5 - 7.5	8.9 on 6.5	26.6	12	788	1620@35
P215/70R15	97T	BW	46897	5.5 - 7.5	8.9 on 6.5	26.6	12	788	1620@35
P225/70R15	100T	BW	98384	6.0 - 8.0	9.2 on 6.5	27.1	12	773	1753@35
P235/70R15	102T	BW	58568	6.0 - 8.5	9.7 on 7.0	27.7	12	757	1896@35
P215/60R16	94T	BW	84837	5.5 - 8.5	8.9 on 6.5	25.9	11	805	1477@35
P215/65R16	96T	BW	87651	6.0 - 7.0	9.0 on 6.5	26.7	11	782	1565@35
P225/60R16	97T	BW	85562	6.5 - 9.0	9.1 on 6.5	26.5	12	970	1609@35

Michelin® tires and tubes are subject to a continuous development program. Michelin North America reserves the right to change product specifications at any time without notice or obligation.

1. The dimensions shown are average values for tires measured on specified measuring rim width. Individual tires may vary from data shown.

2. Section width varies approximately 0.2" (5mm) for every 0.5" change in rim width. WARNING: Serious or fatal injury may result from improper mounting, from under-inflation/over-inflation/over-loading or from tire damage due to abusive use. For proper mounting, see tire dealer. For proper tire size and inflation pressure, consult Tire Information Placard in vehicle.

For high-speed driving, additional inflation pressure and possibly reduced tire loading and/or upsizing is required. In the absence of specific recommendations by the vehicle manufacturer, use the following guidelines based on those in the European Tyre and Rim Technical Organization Standards Manual. For speeds over 100 mph, load and inflation must be adjusted according to the table below.

**T-Speed Rated Sizes**

Maximum Speed (mph)	100	106	112	118
Inflation Increase (psi)	0	1	2	3
Load Capacity (% of max.)	100	100	100	100

Inflation pressure increase must not exceed the maximum pressure branded on the tire sidewall. When a customer requests a replacement tire with a lower speed rating than the original equipment tire, you must clearly communicate to him or her that the handling of the vehicle may be different, and that its maximum speed capability is limited to that of the lowest speed-rated tire on the vehicle. Exceeding the lawful speed limit is neither recommended nor endorsed.

**INCREASED HYDROPLANING RESISTANCE** and tread life due to special water-isolating lateral grooves.

**EXCEPTIONAL WET TRACTION**, thanks to see-through circumferential grooves that drain water from the contact patch fast while promoting high efficiency throughout the tread's life.

**EXCELLENT STABILITY AND STEERING RESPONSE** in acceleration and braking due to large, variable-compliance shoulder blocks.

**SHARP APPEARANCE WITH NEW DURABLACK™ "STAY BLACK"** rubber compound and sleek sidewall styling.

**DELIVERING EXCEPTIONAL TRACTION AND EXTENDED TREADWEAR**, the Michelin Stress Equilibrium Casing™ distributes loads and wear equally throughout the contact patch.

**IMPROVED WET GRIP, SNOW TRACTION, HEAT RESISTANCE, AND TREAD LIFE** provided by Michelin Smart Compound.

**INCREASED CORNERING** thanks to thousands of biting, interlocking sipes, while stabilizing tread blocks to provide smooth, even wear.

